Technical Specifications

| Foor to top of footrest | 85 | 3.5 |
|--|---|---|
| Top of footrest to top of seat | 445 | 18 |
| Top of seat to top of arms | 250 | 10 |
| Top of arms to top of seat back | 250 | 10 |
| Width between armrests (Wide arm version) | 445 (495) | 17.5 (19.5) |
| Overall width | 620 | 24.5 |
| Overall height | 995 | 38.5 |
| Length of arms from seat back | 470 | 18.5 |
| Length of seat base from seat back | 425 | 16.75 |
| Length of footrest | 325 | 12.75 |
| Width of footrest | 310 | 12.25 |
| Front of footrest to stringer | 546 | 21.5 |
| Back of seat to stringer | 13 | 0.5 |
| Folded width | 280 | 11 |
| Minimum width required to swivel at top | 645 | 26.25 |
| Distance from front of rail to stringer (Wide arm version) | 210 (235) | 8.25 (19.25) |
| | Top of footrest to top of seat Top of seat to top of arms Top of arms to top of seat back Width between armrests (Wide arm version) Overall width Overall height Length of arms from seat back Length of seat base from seat back Length of footrest Width of footrest Front of footrest to stringer Back of seat to stringer Folded width Minimum width required to swivel at top | Foor to top of footrest Top of footrest to top of seat Top of footrest to top of seat Top of seat to top of arms 250 Top of arms to top of seat back 250 Width between armrests (Wide arm version) 445 (495) Overall width 620 Overall height 1995 Length of arms from seat back 470 Length of seat base from seat back 425 Length of footrest 325 Width of footrest 310 Front of footrest to stringer 546 Back of seat to stringer 13 Folded width 280 Minimum width required to swivel at top 645 |

